

# ULTRA QUIET PORTABLE ELECTRIC OIL FREE AIR COMPRESSORS

Ultra quiet air compressors are designed with induction motors which produce a low RPM, have a 3X longer motor life and offer up to an 80% quieter operation than standard units. For use with air inflation accessories, air brushes, brad nailers & staplers, finish nailers and more.

SPEEDAIRE INNOVATIVE QUIET SYSTEM  
QUIET COMPRESSOR

UP TO **80% QUIETER\*\*\***

\*\*\*BASED ON INTERNAL TESTING AGAINST LEADING NATIONAL BRANDS

**3X**  
LONGER LIFE

## Hand Carry Portable Electric Air Compressors

- Integrated control panel
- Steel carry handle with cushion grip

- Dual Gauges for tool and tank pressure
- Ultra quiet induction motor

- Up to 1000 hrs motor life
- Oil free pump for less maintenance



787U76



787U77

## 1 & 2 Gallon Hot Dog Style Tanks

- Quick coupler included for universal use.
- Large regulator knob for easy operation.
- Drain valve provided for condensate or water removal.
- Rubber feet for shock proof and skid proof operation.
- Safety valve to prevent system over pressurization.
- Metal hooks included for convenient electrical cord storage.

Item No.	Tank Size (Gal)	Output Power (HP*)	Current Rating (Amps)	Input Voltage (Volts)	Max Operating Pressure (PSI**)	Free Air Flow Rate @ 90 PSI (CFM)	Sound Level (dBa***)	Weight (Lbs.)
<b>1 &amp; 2 Gallon Hot Dog Tanks</b>								
787U76	1	0.5	2.8	120	125	0.8	≤ 60	27.2
787U77	2	1.0	7.5	120	125	2.4	≤ 65	41.5

## Replacement Parts

788UR2	Pressure Switch for 787U76 & 787U77
788UR8	Pressure Gauges for 787U76 & 787U77
788UT0	Safety Valve for 787U76 & 787U77
788UT2	Check Valve for 787U76
788UT3	Check Valve for 787U77
788UT5	Regulator Assembly for 787U76 & 787U77
788UT7	Drain Valve for 787U76 & 787U77
788UT8	Couplers for 787U76 & 787U77

## Wheeled Portable Electric Air Compressors

- Integrated control panel
- Dual Gauges for tool and tank pressure
- Up to 1000 hrs motor life
- Ultra quiet induction motor
- Oil free pump for less maintenance

- Drain valve provided for condensate or water removal
- Rubber feet for shockproof and skid proof operation
- Safety valve to prevent system over pressurization
- Steel carry handle with cushion grip for ease of movement and storage
- Large regulator knob for easy operation

## 4.5 Gallon Twin Stack Style Tanks

- Integral accessory storage compartment for air tool accessories.



787U78

Item No.	Tank Size (Gal)	Output Power (HP*)	Current Rating (Amps)	Input Voltage (Volts)	Max Operating Pressure (PSI**)	Free Air Flow Rate @ 90 PSI (CFM)	Sound Level (dBa***)	Weight (Lbs.)
<b>4.5 Gallon Twin Stack Tanks</b>								
787U78	4.5	1.3	8.5	120	150	3.0	≤ 65	62

## Replacement Parts

788UR4	Pressure Switch for 787U78
788UR5	Wheels for 787U78
788UR8	Pressure Gauges for 787U78
788UT1	Safety Valve for 787U78
788UT3	Check Valve for 787U78
788UT5	Regulator Assembly for 787U78
788UT7	Drain Valve for 787U78
788UT8	Couplers for 787U78

# ULTRA QUIET PORTABLE ELECTRIC OIL FREE AIR COMPRESSORS (CNTD')

## Wheeled Portable Electric Air Compressors (Continued)

SPEEDAIRE INNOVATIVE QUIET SYSTEM  
QUIET COMPRESSOR

UP  
TO  
**80% QUIETER\*\*\***  
\*\*\*BASED ON INTERNAL TESTING AGAINST LEADING NATIONAL BRANDS

**3X**  
LONGER LIFE



787U79

### 10, 20 & 26 Gallon Vertical Style Tanks

- Vertical tank design minimizes floor space required.
- Reinforced steel frame protects pump and motor assembly.
- (2) Quick couplers included for universal use.

Item No.	Tank Size (Gal)	Output Power (HP*)	Current Rating (Amps)	Input Voltage (Volts)	Max Operating Pressure (PSI**)	Free Air Flow Rate @ 90 PSI (CFM)	Sound Level (dBa***)	Weight (Lbs.)
<b>10, 20 &amp; 26 Gallon Vertical Style Tanks</b>								
787U79	10	1.5	11	120	150	4.0	≤70	85
787U80	20	1.8	12	120	150	4.5	≤72	115
787U81	26	2.0	15	120	150	5.2	≤73	123

### Replacement Parts


788UR3	Pressure Switch for 787U79, 787U80 & 787U81
788UR6	Wheels for 787U79
788UR7	Wheels for 787U80 & 787U81
788UR9	Pressure Gauges for 787U79, 787U80 & 787U81
788UT1	Safety Valve for 787U79, 787U80 & 787U81
788UT4	Check Valve for 787U79, 787U80 & 787U81
788UT6	Regulator Assembly for 787U79, 787U80 & 787U81
788UT7	Drain Valve for 787U79, 787U80 & 787U81
788UT8	Couplers for 787U79, 787U80 & 787U81



787U80



787U81



All specifications contained within are subject to change.  
All air compressors are ETL certified and conform to UL Standard 1017.  
\* Horsepower and air delivery value measured in accordance with ISO1217.  
\*\* Maximum air pressure before shut off.  
\*\*\* Sound level is measured 3 feet from equipment.