



JACKET WRAP

PRODUCT DESCRIPTION:

JACKET WRAP is linear low-density polyethylene film used to compress and consolidate the ROCKET WRAP composite repair system or SEAL WRAP during the curing process.

FEATURES:

- Max Service temperature: 225°F (107°C)
- Securely compacts saturated carbon fiber or water activated fiberglass wrap around the repair area
- Unsurpassed combination of strength and elasticity

INSTRUCTIONS FOR USE:

1. After the final piece of pipe wrap has been applied, start to wrap loosely until JACKET WRAP overlaps.
2. Pulling tightly, continue wrapping in a spiral fashion with a 50% overlap (be sure to prevent ROCKET FABRIC or SEAL WRAP from shifting).
3. Apply JACKET WRAP past fabric edge / primer.
4. Once epoxy or water activated resin has set, it can be removed.

PHYSICAL PROPERTIES:

Color: Orange
Gauge: 250

STORAGE AND HANDLING:

The shelf life of JACKET WRAP is unlimited. For best results, store in a cool, dry place out of direct sunlight.

PACKAGING:

5" x 200 Ft Roll
12" x 700 Ft Roll

LIMITED WARRANTY

For warranty information please visit

http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@jetlube.com