

DESCRIPTION

2-part rubber sealant compound.
Dark Brown color when mixed.

TEMPERATURE RANGE

-50°F to 230°F

APPLICATIONS

Threads, Flanges.

CHEMICAL COMPATIBILITY

For Use On: Gasoline, Hydrocarbons, Solvents (Mineral Spirits, Naphta etc.), Alcohol's, Water, HF Acid (Under 25%), Sodium Hydroxide 50%, Transformer Oils.

CURING

Work life 1 hour at 70°F. Work life is significantly reduced at elevated temperatures (30 min. or less above 75°F). Product can be kept on ice to extend application life.

CLEANING

Use Xylene or Toluene to clean equipment of uncured sealant.

SHELF LIFE

Two years in original unopened containers. Store at less than 80°F.

PACKAGED

Pint and Quart kits.
Other sizes available upon request.

DIRECTIONS

Please be advised that we recommend a top and bottom ring of braided packing still be installed for containment, especially when tolerances are in question.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@deaconindustries.com or write to the Sales Department at the address below.