

## GEN 3 FEATURES

The Gen3, BRICK<sup>®</sup> is now built with “on-site” cable replacement features. Its distinguishing feature is the green Bend Radius Sleeve (\*Patent Pending) on the cable connection points. Replacement pieces include the power supply box, the cable, and the light head.



GLOW  
• in • the •  
DARK

Optional  
Safety Bumpers  
Available

Bend Radius Sleeve  
(patent pending)



## Product Features

Approved for:	Class I, Div 1 & 2, Groups C & D Class II, Div 1 & 2, Groups E, F, & G CSA Zones 1 & 2; Zones 20, 21, & 22
Conforms to:	UL Stds 153, 781, 844
Certified to:	CSA Stds C22.2#s 12, 25, 137
Suitable for:	Wet Location Use
Certified:	Portable Luminaire (Portable Luminaire)
Temperature Rating:	T-code: T5 (-20°C to +40°C); T4 (-25°C to +100°C)
LED Color:	~6000K, CRI >70
Light Head Power:	36 VDC, 2.4A (A&C Models)
Light Output:	50,000 lux at 1', >11,500 lumens
Optic:	60° Reflective Optic Beam Angle
Weight:	10 lbs (light head only)
Dimensions:	• Light head, handles, bumpers: 12¾" x 6½" x 5¼" • Bend Radius Enforcement Sleeve (connecting cord to light head): 10.1875" x 1.5625"
Body Material:	Machined solid blocks of 6061-T6 Aluminum Polyurethane Bumpers
Accessories:	• Blast Shields • Dome Diffuser, etc. (See Back)
Mounting Options:	Mechanical / Magnetic Mounting (See Back)
Additional Features:	• Variable intensity light control (Dimmer switch option available) • Thermally controlled for comfortable handling • Bend Radius Sleeve (patent pending) • strain relief for electrical cord connections.



The BRICK<sup>®</sup>  
shown lighting Fuel Tank